

Cat6 - FTP - STRANDED - PVC

Category	PATCH F/UTP CAT6-4P-PVC																																																																		
Reference	ISO/IEC 11801 TIA-568-C.2																																																																		
CPR Classification	Fca																																																																		
Material	Soepel - 100% koper																																																																		
Shielding class	FTP																																																																		
AWG	26	Technical performance (<30m):																																																																	
Diameter cable	6,1 mm	<table><tr><th>Frequency (Mhz)</th><th>RL ≥dB</th><th>ATT ≤dB</th><th>NEXT ≥dB</th><th>DELAY ≤ns</th></tr><tr><td>1</td><td>19.1</td><td>3.0</td><td>65.0</td><td>521</td></tr><tr><td>4.0</td><td>21.0</td><td>3.5</td><td>64.1</td><td>504</td></tr><tr><td>8.0</td><td>21.0</td><td>5.0</td><td>59.4</td><td>500</td></tr><tr><td>10.0</td><td>21.0</td><td>5.5</td><td>57.8</td><td>498</td></tr><tr><td>16.0</td><td>20.0</td><td>7.0</td><td>54.6</td><td>496</td></tr><tr><td>20.0</td><td>19.5</td><td>7.9</td><td>53.1</td><td>495</td></tr><tr><td>25.0</td><td>19.0</td><td>8.9</td><td>51.5</td><td>495</td></tr><tr><td>31.25</td><td>18.5</td><td>10.0</td><td>50.0</td><td>494</td></tr><tr><td>62.5</td><td>16.0</td><td>14.4</td><td>45.1</td><td>492</td></tr><tr><td>100</td><td>14.0</td><td>18.6</td><td>41.8</td><td>491</td></tr><tr><td>200</td><td>11.0</td><td>27.4</td><td>36.9</td><td>490</td></tr><tr><td>250</td><td>10.0</td><td>31.1</td><td>35.3</td><td>490</td></tr></table>	Frequency (Mhz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	DELAY ≤ns	1	19.1	3.0	65.0	521	4.0	21.0	3.5	64.1	504	8.0	21.0	5.0	59.4	500	10.0	21.0	5.5	57.8	498	16.0	20.0	7.0	54.6	496	20.0	19.5	7.9	53.1	495	25.0	19.0	8.9	51.5	495	31.25	18.5	10.0	50.0	494	62.5	16.0	14.4	45.1	492	100	14.0	18.6	41.8	491	200	11.0	27.4	36.9	490	250	10.0	31.1	35.3	490
Frequency (Mhz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	DELAY ≤ns																																																															
1	19.1	3.0	65.0	521																																																															
4.0	21.0	3.5	64.1	504																																																															
8.0	21.0	5.0	59.4	500																																																															
10.0	21.0	5.5	57.8	498																																																															
16.0	20.0	7.0	54.6	496																																																															
20.0	19.5	7.9	53.1	495																																																															
25.0	19.0	8.9	51.5	495																																																															
31.25	18.5	10.0	50.0	494																																																															
62.5	16.0	14.4	45.1	492																																																															
100	14.0	18.6	41.8	491																																																															
200	11.0	27.4	36.9	490																																																															
250	10.0	31.1	35.3	490																																																															
Length	305m																																																																		
Transfer frequency	250.0 MHz																																																																		
Bending radius	-																																																																		
Tensile Strength (Mpa)	≥ 13.5																																																																		
Type of cable sheathing	PVC																																																																		
Color	Grey	<table><tr><th>Frequency (Mhz)</th><th>PSNEXT ≥dB</th><th>ELFEXT ≤dB</th><th>PSELFEXT ≥dB</th></tr><tr><td>1</td><td>62.0</td><td>64.2</td><td>61.2</td></tr><tr><td>4.0</td><td>61.8</td><td>52.1</td><td>49.1</td></tr><tr><td>8.0</td><td>57.0</td><td>46.1</td><td>43.1</td></tr><tr><td>10.0</td><td>55.5</td><td>44.2</td><td>41.2</td></tr><tr><td>16.0</td><td>52.2</td><td>40.1</td><td>37.1</td></tr><tr><td>20.0</td><td>50.7</td><td>38.2</td><td>35.2</td></tr><tr><td>25.0</td><td>49.1</td><td>36.2</td><td>33.2</td></tr><tr><td>31.25</td><td>47.5</td><td>34.3</td><td>31.3</td></tr><tr><td>62.5</td><td>42.7</td><td>28.3</td><td>25.3</td></tr><tr><td>100</td><td>39.3</td><td>24.2</td><td>21.2</td></tr><tr><td>200</td><td>34.3</td><td>18.2</td><td>15.2</td></tr><tr><td>250</td><td>32.7</td><td>16.2</td><td>13.2</td></tr></table>	Frequency (Mhz)	PSNEXT ≥dB	ELFEXT ≤dB	PSELFEXT ≥dB	1	62.0	64.2	61.2	4.0	61.8	52.1	49.1	8.0	57.0	46.1	43.1	10.0	55.5	44.2	41.2	16.0	52.2	40.1	37.1	20.0	50.7	38.2	35.2	25.0	49.1	36.2	33.2	31.25	47.5	34.3	31.3	62.5	42.7	28.3	25.3	100	39.3	24.2	21.2	200	34.3	18.2	15.2	250	32.7	16.2	13.2													
Frequency (Mhz)	PSNEXT ≥dB	ELFEXT ≤dB	PSELFEXT ≥dB																																																																
1	62.0	64.2	61.2																																																																
4.0	61.8	52.1	49.1																																																																
8.0	57.0	46.1	43.1																																																																
10.0	55.5	44.2	41.2																																																																
16.0	52.2	40.1	37.1																																																																
20.0	50.7	38.2	35.2																																																																
25.0	49.1	36.2	33.2																																																																
31.25	47.5	34.3	31.3																																																																
62.5	42.7	28.3	25.3																																																																
100	39.3	24.2	21.2																																																																
200	34.3	18.2	15.2																																																																
250	32.7	16.2	13.2																																																																
Core color	1 - Blue/ White-Blue																																																																		
	2 - Orange/ White-Orange																																																																		
	3 - Green/ White-Green																																																																		
	4 - Brown/ White-Brown																																																																		
Rip-cord	Yes																																																																		
Packing	Pull box																																																																		